

IN THE SPECIFICATION

On page 5, please replace the paragraph beginning at line 4 with the following paragraph:

With reference to Figure 1, there is shown a control volume injection/aspiration device 10 in accordance with the present invention generally showing a syringe 12 and needle 14 along with a shell 18 for receiving a syringe body 20, see Figures 2-4.

On page 5, please replace the paragraph beginning at line 10 with the following paragraph:

As shown in Figures 2-4, the syringe 12 includes a piston, 24 slidably disposed in the syringe body 24—20 along a syringe body/plunger rack centerline 26, for forcing medicament through the needle 14. A plunger rack 28 is slidably disposed within the shell 18 along the centerline 26 and coupled to the piston 24 at a front end 30 thereof.

On page 6, please replace the paragraph beginning at line 4 with the following paragraph:

The operating control 34 includes a button 48 manually accessible from outside of the shell 18 and a control rod 50 disposed in a parallel relationship with the syringe body/plunger rack centerline as can be seen in Figures 2-4. ~~an~~An injecting pawl 54 is pivot 56 mounted to an end 58 of the rod 50 and is limited in rotation so that forward motion of the button 48 from a neutral position, as shown

3011

in Figure 2, causes the injecting pawl 54 to engage plunger rack teeth 62.